A2200

Release film

Ideally suited to infusion applications

Features and Benefits

- Cost optimized, very flexible release film, ideal for use in resin infusion.
- Colored clear orange to allow resin front to be clearly viewed during infusion and to aid complete removal when de-bagging.
- High conformability with good elongation compliment the film’s excellent release characteristics.
- Suitable for use with epoxy, polyester and vinylester resins, although it is advisable that a test piece is produced prior to committing to a full scale infusion in order to ensure that compatibility and performance meet desired standards.
- Available perforated or non-perforated.

PROPERTIES

Maximum use temperature	120°C	248°F
Color	Clear orange	
Film	PE	
Standard perforation patterns	Contact us for full details	
Tensile strength (at break)	35MPa	5076psi
Elongation (at break)	580%	
Density	0.953g/cm³	0.55oz/in³

AVAILABILITY

Thicknesses	25µm	0.001in
Standard widths	Up to 2m	Up to 80in
Standard length	500m	547yd

STORAGE

Store in original packaging

HEALTH & SAFETY

Please refer to the product MSDS for safe handling, personal protective equipment recommendations and disposal considerations.

DISCLAIMER: The data and information provided in this document have been obtained from carefully controlled samples and are considered to be representative of the product described. Solvay does not express or imply any guarantee or warranty of any kind including, but not limited to, the accuracy, the completeness or the relevance of the data and information set out herein. Because the properties of this product can be significantly affected by the fabrication and testing techniques employed, and since Solvay does not control the conditions under which its products are tested and used, Solvay cannot guarantee the properties provided will be obtained with other processes and equipment. No guarantee or warranty is provided if the product is adapted for a specific use or purpose. Solvay declines any liability with respect to the use made by any third party of the data and information contained herein. Solvay has the right to change any data or information when deemed appropriate. All trademarks are the property of their respective owners. ©2017, Solvay. All rights reserved.

Solvay
Composite Materials HQ
4500 McGinnis Ferry Rd
Alpharetta, GA 30005-3914 USA

21 March 2013

SOLVAY
asking more from chemistry®